



Aluminum Black Coated Driver Box



Tested To Comply With :

UL 263 , ASTM E 119 & CAN/ULC S 101

Specification	
Fire Rated 4" Slim Round Panel	
Size	4.9"x0.8" (Lamp) 3.3"x3.3"x1.2" (Driver)
Beam Angle	140°
Input	120V 60Hz
Power Factor	>0.9
Dimmable	Yes
Power (W)	10W
Luminous Flux	750LM
Color Temperature	2700K-3000K-3500K-4000K-5000K
CRI	>80
SDCM	<7
Life Tume (Hrs)	50000
Certification Requirements	EIL / ES / 5 Years / UL 263 / ASTM E119 / CAN/ULC S101



Features

- Safe - This downlight is IC Rated and airtight junction box, protecting from overheating and designed to be installed in the ceiling surrounded by insulation.

It is ETL certified, which means it has met the nationality recognized safety requirements.

- Energy Efficient - With Energy Star labeled, it consumes only 10 watts, equivalent to 60W halogen. That's so easy to save up to %90 on the electric bill.

- Long Lifespan - The lifespan is as long as 50,000 hours. we provide 5 years warranty and lifetime technical support. Tested to comply with UL 263, ASTM E119 & CAN/ULC S101.

