

Slim Integrated T5 LED(Linkable)



Specifications

Lumen Output	250LM	500LM	900LM	1300LM	1800LM
Power	3W	5W	9W	13W	18W
Length(Inch)	0.5ft	1ft	2ft	3ft	4ft
Lumen Efficiency	100lm/w				
CCT	3000K/4000K/5000K				
CRI	>80Ra				
Input Voltage	120V/ 60Hz				
Power Factor	0.9				
Beam angle	135°				
Operating Temperature	-20~+45 C				
Dimmable	Yes				
CERTIFICATION	cUL				
Life time (Hrs)	50000hrs				

Safety


Comply with UL Requirement, safety in use.RoHS compliance.
Ecodesign. Replacement incandescent:

Features

working voltage :108~132V
No flicker, uniform light. Compatible to traditional lamps.

Application

Operating Temperature: -20~+45°C
Indoor Basic Lighting and Directional Lighting.
Replace incandescent/halogen/CFL lamps.



Compatible Dimmer List

Dimmer Brand
Lutron
Levitation
Lutron
Lutron
Levitation
MACL
Lutron

Integrated T5 LED (Linkable)




Power Cord
(Sell Separately for 1ft & 2ft)



connecting cable
(Sell Separately)



3.93ft power cord with plug on one end and another male end
(Sell Separately)






wire box with female end & on/off switch
(Sell Separately)

HARDWARE CONTENTS (Included in package)

  x2 Mounting Screws (4x22mm)

 x2 Clips

  x2 Mounting Screws (4x16mm)

 x2 Roll plug

 female end cap

3 3/4" Knock outs

Link with Male End of T5 Fixture/ connecting cable (sold separately)

