



Description

The Elakeview LED Canopy caters to a wide range of commercial and industrial applications, ensuring versatility and adaptability in lighting design.



Features

- ETL
- 120-277V Optional
- High Efficacy Up To 130LM/W
- CCT Tunable Available
- Wattage Tunable Available
- Microwave Motion, Photocell Sensor/ Emergency Battery Backup Optional
- Unique Design, Strong Extruded Lamp Body
- Lifespan: >50,000Hrs

Applications

- Parking Garages
- Gas Stations

Ordering Information



| Model | DLC Product ID (Delisted) | Voltage | Wattage | Efficacy | Lumens | CCT | Size |
|-------------|---------------------------|----------|---------|----------|--------|-------|----------------|
| CP40WUNV50K | PLY7IYUAP51W | 120-277V | 40W | 134LM/W | 4800LM | 5000K | 10 X 10 X 4.1" |
| CP40WUNV40K | PLGI2OHDTSQ2 | 120-277V | 40W | 130LM/W | 5092LM | 4000K | 10 X 10 X 4.1" |
| CP40WUNV50K | PLY7IYUAP51W | 120-347V | 45W | 134LM/W | 5255LM | 5000K | 10 X 10 X 4.1" |
| CP70W34740K | PL4I8M1CIS8I | 120-277V | 70W | 130LM/W | 8400LM | 4000K | 10 X 10 X 4.1" |
| CP40WUNV40K | CP40WUNV40K | 120-277V | 70W | 134LM/W | 8740LM | 5000K | 10 X 10 X 4.1" |
| CP70WUNV40K | PL9IDSM9CIYK | 277-480V | 70W | 120LM/W | 8400LM | 4000K | 10 X 10 X 4.1" |

Dimensions

