



## Description

The Elakeview LED Canopy caters to a wide range of commercial and industrial applications, ensuring versatility and adaptability in lighting design.



## Features

- ETL
- 120-347V Optional
- High Efficacy Up To 134LM/W
- CCT Tunable Available
- Wattage Tunable Available
- Microwave Motion, Photocell Sensor/ Emergency Battery Backup Optional
- Unique Design, Strong Extruded Lamp Body
- Lifespan: >50,000Hrs

## Applications

- Parking Garages
- Gas Stations

## Ordering Information



Model	DLC Product ID (Delisted)	Voltage	Wattage	Efficacy	Lumens	CCT	Size
CP40WUNV50K	PLY7IYUAP51W	120-277V	40W	134LM/W	4800LM	5000K	10 X 10 X 4.1"
CP40WUNV40K	PLGI2OHDTSQ2	120-277V	40W	130LM/W	5092LM	4000K	10 X 10 X 4.1"
CP40WUNV50K	PLY7IYUAP51W	120-347V	45W	134LM/W	5255LM	5000K	10 X 10 X 4.1"
CP70W34740K	PL4I8M1CIS8I	120-277V	70W	130LM/W	8400LM	4000K	10 X 10 X 4.1"
CP40WUNV40K	CP40WUNV40K	120-277V	70W	134LM/W	8740LM	5000K	10 X 10 X 4.1"
CP70WUNV40K	PL9IDSM9CIYK	277-480V	70W	120LM/W	8400LM	4000K	10 X 10 X 4.1"

## Dimensions

